



[www.euroncap.com](http://www.euroncap.com)

EUROPEAN NEW CAR  
ASSESSMENT PROGRAMME

# Technical Bulletin

## **IR-TRACC Absolute Length and Angle Calibration**

**Version 1.0**

**November 2014**

**TB 017**

Title	IR-TRACC Absolute Length and Angle Calibration
Version	1.0
Document Number	TB017
Author	Richard Schram
Date	November 2014
Related Documents	Side Impact Mobile Deformable Barrier and Oblique Pole Side Impact Test Protocol
Status	Information
Application Date	January 2015

**Copyright ©Euro NCAP 2014** - This work is the intellectual property of Euro NCAP. Permission is granted for this material to be shared for non-commercial, educational purposes, provided that this copyright statement appears on the reproduced materials and notice is given that the copying is by permission of Euro NCAP. To disseminate otherwise or to republish requires written permission from Euro NCAP.

# 1 Calibration of 2D IR-TRACC

From 2015 onwards, Euro NCAP uses the WorldSID 50<sup>th</sup> dummy in side impact tests. The dummy is equipped with 2D-IRTRACC sensors from which the maximum lateral rib deflection is determined. The lateral deflection can be calculated from the actual IR-TRACC compression and the measured rotation.

To be able to accurately calculate the theoretical lateral deflection, a dedicated calibration procedure has been proposed. Any IR-TRACC installed in the WorldSID dummy and used in Euro NCAP side impact tests will need to be calibrated as described below.

## 1.1 Calibration procedure

The calibration procedure used for all Euro NCAP tests will be performed as reported in Humanetics Service Bulletin, IR-TRACC Absolute Length Calibration, which can be found on <http://www.humaneticsatd.com/tech-sheets-service-bulletins>.

## 1.2 Lateral Rib Deflection

For all WorldSID rib deflection measurements used in official Euro NCAP tests, the purely lateral displacement is used which is determined using the following formula (also detailed in TB 021):

$$Dy_{rib} = \max(D_y(t) - D_y(0))$$

with:

$$D_y(t) = L(t) \cdot \cos(\alpha(t))$$

L(t) Filtered IR-TRACC length

$\alpha(t)$  Filtered IR-TRACC rotation

$D_y(0)$  Lateral Rib Displacement @ t=0