



www.euroncap.com

EUROPEAN NEW CAR
ASSESSMENT PROGRAMME

Technical Bulletin

Data format and Injury Criteria Calculation

Version 1.0

**October 2014
TB 021**

Copyright 2014 ©Euro NCAP - This work is the intellectual property of Euro NCAP. Permission is granted for this material to be shared for non-commercial, educational purposes, provided that this copyright statement appears on the reproduced materials and notice is given that the copying is by permission of Euro NCAP. To disseminate otherwise or to republish requires written permission from Euro NCAP.

Title	Data format and Injury Criteria Calculation
Version	1.0
Document Number	TB021
Author	R Schram
Date	28 October 2014
Related Documents	Frontal ODB, FW, Side Barrier, Side Pole Impact, Whiplash and Pedestrian Test Protocols
Status	2015 Protocol Update
Application Date	1 January 2015

Preface

Euro NCAP contracts a number of different test laboratories in Europe to perform the official Euro NCAP tests. This Technical Bulletin describes how the test data should be acquired and supplied to Euro NCAP to ensure consistency throughout all laboratories.

Table of Contents

Page No.

1	TEST DATA	7
1.1	Data Format	7
1.2	Channel names and filters	10
2	INJURY CRITERIA CALCULATION	17
2.1	Head criteria	17
2.2	Neck criteria	18
2.3	Shoulder criteria	19
2.4	Chest criteria	20
2.5	Abdomen criteria	21
2.6	Lower extremities criteria	22

1 TEST DATA

1.1 Data Format

All test data needs to be provided in ISO-MME 1.6 or ISO-MME 2.0 formats and needs to be fully compliant with the ISO/TS 13499 standard.

1.1.1 Folder structure

The folder structure and the files contained in these folders follow the ISO/TS 13499 standard. The main directory contains seven folders and two files as detailed in the paragraphs below.

1.1.1.1 ISO-MME 1.6

The following folders and files (comment files when needed) need to be provided for every test performed, where the test number is the one as provided by Euro NCAP:

<test number>	Main Directory
- Channel	Sub Directory
o <test number>.xxx	Channel data file
o <test number>.chn	Channel information file
- Document	Sub Directory
o <name of document file 1>	Document file 1
o ...	
o <name of document file d>	Document file d
o <test number>_Document.txt	Document comment file
- Movie	Sub Directory
o <name of movie file 1>	Movie file 1
o ...	
o <name of movie file m>	Movie file m
o <test number>_Movie.txt	Movie comment file
- Object	Sub Directory
o <test number>_Reference.txt	Reference system comment file
o <name of object file 1>	Object information file 1
o ...	
o <name of object file o>	Object information file o
o <test number>_Object.txt	Object comment file
- Photo	Sub Directory
o <name of photo file 1>	Photo file 1
o ...	
o <name of photo file p>	Photo file p
o <test number>_Photo.txt	Photo comment file
- Report	Sub Directory
o <name of report file 1>	Report file 1
o ...	
o <name of report file r>	Report file r
o <test number>_Report.txt	Report comment file
- Static	Sub Directory
o <name of static measurement file>	Static measurement file
o <test number>_Static.txt	Static measurement comment file
- <test number>.mme	Test information file
- <test number>.txt	Test comment file

1.1.1.2 ISO-MME 2.0

The following folders and files (comment files when needed) need to be provided for every test performed, where the test number is the one as provided by Euro NCAP:

<test number>	Main Directory
- Channel	Sub Directory
o <test number>_Channel.mmi	Channel information file
o <name of channel file 1>.mmd	Channel data file 1
o ...	
o <name of channel file c>.mmd	Channel data file c
o <test number>_Channel.txt	Channel comment file
- Document	Sub Directory
o <test number>_Document.mmi	Document information file
o <name of document file 1>	Document file 1
o ...	
o <name of document file d>	Document file d
o <test number>_Document.txt	Document comment file
- Movie	Sub Directory
o <test number>_Movie.mmi	Movie information file
o <test number >_Movie.mmd	Movie data file
o <name of movie file 1>	Movie file 1
o ...	
o <name of movie file m>	Movie file m
o <test number>_Movie.txt	Movie comment file
- Object	Sub Directory
o <test number>_Reference.mmi	Reference system information file
o <test number >_Reference.mmd	Reference system data file
o <test number>_Reference.txt	Reference system comment file
o <name of object file 1>	Object information file 1
o ...	
o <name of object file o>	Object information file o
o <test number>_Object.txt	Object comment file
- Photo	Sub Directory
o <test number>_Photo.mmi	Photo information file
o <name of photo file 1>	Photo file 1
o ...	
o <name of photo file p>	Photo file p
o <test number>_Photo.txt	Photo comment file
- Report	Sub Directory
o <test number>_Report.mmi	Report information file
o <name of report file 1>	Report file 1
o ...	
o <name of report file r>	Report file r
o <test number>_Report.txt	Report comment file
- Static	Sub Directory
o <test number>_Static.mmi	Static measurement info file
o <test number>_Static.mmd	Static measurement data file
o <test number>_Static.txt	Static measurement comment file
- <test number>.mme	Test information file
- <test number>.txt	Test comment file

1.1.2 MME-file

The mme-file shall contain at least the following header:

```
Data format edition number    1.6 or 2.0
....
Customer name                 Euro NCAP
Customer test ref number      <test number>
Title                         Euro NCAP <year of test>
Type of the test              <see list in 1.1.2.1>
Subtype of the test           <see list in 1.1.2.1>
Regulation                    <protocol version>
Name of test object 1         <make and model>
Class of test object 1        <Euro NCAP vehicle class>
Ref. number of test object 1  <VIN number>
...
```

1.1.2.1 List with type and subtype of the test

Euro NCAP test	Type of Test	Subtype of test
Frontal ODB	Frontal	ODB
Frontal FW	Frontal	FW
Side MDB	Side	MDB
Side Pole	Side	Pole
Whiplash	Whiplash	Low Medium High
Pedestrian	Pedestrian	Headform Upper Legform Lower Legform

1.2 Channel names and filters

For each dummy, impactors and test objects used in the different Euro NCAP tests the following channel names shall be used. All channels shall be supplied unfiltered/prefiltered. The appropriate filters for calculation of injury criteria and plotting of these channels will be performed by the analysis software used.

1.2.1 Hybrid III 50% Male

Location	Parameter	ISO code	CFC	Injury Calculation
Head	Accelerations, A_x A_y A_z	??HEAD0000H3AC[X,Y,Z]P	1000	Peak Resultant acceleration HIC ₁₅ Resultant 3msec cumulative exceedence
Neck	Forces, F_x F_y F_z	??NECKUP00H3FO[X,Y,Z]P	1000	Tension continuous exceedence Shear (F_x) continuous exceedence Peak Extension (M_y)
	Moments, M_x M_y M_z	??NECKUP00H3MO[X,Y,Z]P	600	
Chest	Accelerations, A_x A_y A_z	??CHST0000H3AC[X,Y,Z]P	180	Peak resultant acceleration Resultant 3 msec cumulative exceedence Peak deflection Viscous Criterion
	Deflection, D_{chest}	??CHST0003H3DSXP	180	
Pelvis	Accelerations, A_x A_y A_z	??PELV0000H3AC[X,Y,Z]P	600	
Lumbar Spine	Forces, F_x F_z	??LUSP0000H3FO[X,Z]P	600	
	Moments, M_y	??LUSP0000H3MOYP	600	
Femurs (L & R)	Forces, F_z	??FEMR[LE,RI]00H3FOZP	600	Compressive Axial Force ($-F_z$) continuous exceedence
Knees (L & R)	Displacements, D_{knee}	??KNSL[LE,RI]00H3DSXP	180	Peak displacement
Upper Tibia (L & R)	Forces, F_x F_z	??TIBI[LE,RI]UPH3FO[X,Z]P	600	Peak Tibia Compression ($-F_z$) Tibia Index
	Moments, M_x M_y	??TIBI[LE,RI]UPH3MO[X,Y,Z]P	600	
Lower Tibia (L & R)	Forces, F_x F_z (F_y)	??TIBI[LE,RI]LOH3FO[X,Y,Z]P	600	Peak Tibia Compression ($-F_z$) Tibia Index
	Moments, M_x M_y	??TIBI[LE,RI]LOH3MO[X,Y,Z]P	600	

1.2.1.1 Hybrid III 5% Female

Location	Parameter	ISO code	CFC	Injury Calculation
Head	Accelerations, $A_x A_y A_z$??HEAD0000HFAC[X,Y,Z]P	1000	Peak Resultant acceleration HIC ₁₅ Resultant 3msec cumulative exceedence
Neck	Forces, $F_x F_y F_z$??NECKUP00HFFO[X,Y,Z]P	1000	Tension continuous exceedence Shear (F_x) continuous exceedence Peak Extension (M_y)
	Moments, $M_x M_y M_z$??NECKUP00HFMO[X,Y,Z]P	600	
Chest	Accelerations, $A_x A_y A_z$??CHST0000HFAC[X,Y,Z]P	180	Peak resultant acceleration Resultant 3 msec cumulative exceedence Peak deflection Viscous Criterion
	Deflection, D_{chest}	??CHST0003HFDSXP	180	
Pelvis	Accelerations, $A_x A_y A_z$??PELV0000HFAC[X,Y,Z]P	600	
Iliac (L & R)	Forces, F_x	??ILAC[LE,RI]00HFFOXP	180	
	Moments, M_y	??ILAC[LE,RI]00HFMOYP	180	
Lumbar Spine	Forces, $F_x F_z$??LUSP0000HFFO[X,Z]P	180	
	Moments, M_y	??LUSP0000HFMOYP	180	
Femurs (L & R)	Forces, F_z	??FEMR[LE,RI]00HFFOZP	600	Compressive Axial Force ($-F_z$) Continuous exceedence
Knees (L & R)	Displacements, D_{knee}	??KNSL[LE,RI]00HFDSXP	180	Peak displacement
Upper Tibia (L & R)	Forces, $F_x F_z$??TIBI[LE,RI]UPHFFO[X,Z]P	600	Peak Tibia Compression ($-F_z$) Tibia Index
	Moments, $M_x M_y$??TIBI[LE,RI]UPHFMO[X,Y,Z]P	600	
Lower Tibia (L & R)	Forces, $F_x F_z (F_y)$??TIBI[LE,RI]LOHFFO[X,Y,Z]P	600	Peak Tibia Compression ($-F_z$) Tibia Index
	Moments, $M_x M_y$??TIBI[LE,RI]LOHFMO[X,Y,Z]P	600	

1.2.1.2 WorldSID 50% Male

Location	Parameter		CFC	Injury Calculation
Head	Accelerations, $A_x A_y A_z$??HEAD0000WSAC[X,Y,Z]P	1000	HIC ₁₅ Peak acceleration 3msec exceedence (cumulative)
Neck	Forces, $F_x F_y F_z$??NECKUP00WSFO[X,Y,Z]P	1000	
	Moments, $M_x M_y M_z$??NECKUP00WSMO[X,Y,Z]P	600	
Shoulder	Forces, F_x, F_y, F_z	??SHLD[LE,RI]00WSFO[X,Y,Z]P	600	Peak lateral force
	Displacement, D	??SHRI[LE,RI]00WSDS0P	180	Peak displacement
	Rotation, α	??SHRI[LE,RI]00WSANZP	180	Viscous criterion
Thorax	Displacement, D	??TRRI[LE,RI][01,02,03]WSDS0P	180	Peak displacement
	Rotation, α	??TRRI[LE,RI][01,02,03]WSANZP	180	Viscous criterion
Abdomen	Displacement, D	??ABRI[LE,RI][01,02]WSDS0P	180	Peak displacement
	Rotation, α	??ABRI[LE,RI][01,02]WSANZP	180	Viscous criterion
T12	Accelerations, $A_x A_y A_z$??THSP1200WSAC[X,Y,Z]P	180	Peak acceleration
Pelvis	Accelerations, $A_x A_y A_z$??PELV0000WSAC[X,Y,Z]P	600	Peak acceleration
	Forces, F_y	??PUBC0000WSFOYP	600	Peak force
Femoral Neck	Forces, $F_x F_y F_z$??FEMR[LE,RI]00WSFO[X,Y,Z]P	600	Peak force

1.2.1.3 BioRID-II

Location	Parameter		CFC	Injury Calculation
Head	Accelerations, $A_x A_y A_z$??HEAD0000BRAC[X,Y,Z]P	60	NIC
	Velocity, V_x	??HEAD0000BRVEXV	30	Head rebound velocity
	Contact	??HERE000000EV00		Head contact time
Cervical Spine	Accelerations, $A_x A_z$??CESP0400BRAC[X,Z]P	60	
Neck Upper	Forces, $F_x F_y F_z$??NECKUP00BRFO[X,Y,Z]P	1000	Nkm Neck shear (+F _x) Neck tension (+F _z)
	Moments, $M_x M_y M_z$??NECKUP00BRMO[X,Y,Z]P	600	Nkm
Neck Lower	Forces, $F_x F_y F_z$??NECKLO00BRFO[X,Y,Z]P	1000	
	Moments, $M_x M_y M_z$??NECKLO00BRMO[X,Y,Z]P	600	
Thoracic Spine T1 (L & R)	Accelerations, $A_x A_z$??THSP01[LE,RI]BRAC[X,Z]P	60	T1-acceleration NIC
Thoracic Spine T8	Accelerations, $A_x A_z$??THSP0800BRAC[X,Z]P	60	
Lumbar Spine	Accelerations, $A_x A_z$??LUSP0100BRAC[X,Z]P	60	
Pelvis	Accelerations, $A_x A_y A_z$??PELV0000BRAC[X,Y,Z]P	60	

1.2.1.4 Q1 ½

Location	Parameter	ISO code	CFC	Injury Calculation
Head	Accelerations, A _x A _y A _z	??HEAD0000Q2AC[X,Y,Z]P	1000	Peak Resultant acceleration Resultant (+ve) 3msec exceedence
Neck	Forces, F _x F _y F _z	??NECKUP00Q2FO[X,Y,Z]P	1000	Peak Tensile Force F _z
	Moments, M _x M _y M _z	??NECKUP00Q2MO[X,Y,Z]P	600	Peak resultant acceleration Resultant (+ve) 3msec exceedence
Chest	Accelerations, A _x A _y A _z	??THSP0000Q2AC[X,Y,Z]P	180	Peak Acceleration
	Deflection	??CHST0000Q2DSXP	180	Peak Resultant acceleration Resultant (+ve) 3msec exceedence

1.2.1.5 Q3

Location	Parameter	ISO code	CFC	Injury Calculation
Head	Accelerations, A _x A _y A _z	??HEAD0000Q3AC[X,Y,Z]P	1000	Peak Resultant acceleration Resultant (+ve) 3msec exceedence
Neck	Forces, F _x F _y F _z	??NECKUP00Q3FO[X,Y,Z]P	1000	Peak Tensile Force F _z
	Moments, M _x M _y M _z	??NECKUP00Q3MO[X,Y,Z]P	600	Peak resultant acceleration Resultant (+ve) 3msec exceedence
Chest	Accelerations, A _x A _y A _z	??THSP0000Q3AC[X,Y,Z]P	180	Peak Acceleration
	Deflection	??CHST0000Q3DSXP	180	Peak Resultant acceleration Resultant (+ve) 3msec exceedence

1.2.1.6 Adult Headform

Location	Parameter	ISO code	CFC	Injury Calculation
Head	Accelerations, A_x A_y A_z	DOHEAD0000PJAC[X,Y,Z]P	1000	HIC ₁₅

1.2.1.7 Small Adult / Child Headform

Location	Parameter	ISO code	CFC	Injury Calculation
Head	Accelerations, A_x A_y A_z	DOHEAD0000PSAC[X,Y,Z]P	1000	HIC ₁₅

1.2.1.8 Upper Legform

Location	Parameter	ISO code	CFC	Injury Calculation
Femur	Forces, F_x	DOFEMR[UP,LO]00PUFOXP	180	Sum of Forces
	Moments, M_y	DOFEMR[UP,MI,LO]00PUMOYP	180	Bending Moment

1.2.1.9 Lower Legform (Flex-PLI)

Location	Parameter	ISO code	CFC	Injury Calculation
Femur	Moments, M_x	DOFEMR[UP,MI,LO]00PFMOXP	180	
Knee	Accelerations, A_y	DOKNEE0000PFACYP	180	
	Displacement, D_{ACL}	DOKNEEAC00PFDSZP	180	ACL/PCL
	Displacement, D_{LCL}	DOKNEELC00PFDSZP	180	
	Displacement, D_{MCL}	DOKNEEMC00PFDSZP	180	MCL
	Displacement, D_{PCL}	DOKNEEPC00PFDSZP	180	ACL/PCL
Tibia	Moments, M_x	DOTIBI[UP,LO]00PFMOXP DOTIBIMI[UP,LO]PFMOXP	180	Tibia Bending Moment

1.2.1.10 Vehicle

Location	Parameter	ISO code	CFC	Injury Calculation
B-Post	Accelerations, Ax Ay	[14,16]BPILLO0000AC[X,Y]P	60	
Seatbelt	Force, F_{seatbelt}	??SEBE0003B3FO0P	60	Seat belt force modifier

1.2.1.11 Trolley

Location	Parameter	ISO code	CFC	Injury Calculation
CoG	Accelerations, Ax	M0MBCRCG0000ACXP	60	

1.2.1.12 Sled

Location	Parameter	ISO code	CFC	Injury Calculation
Sled	Accelerations, Ax	S0SLED000000ACXP	60	

2 INJURY CRITERIA CALCULATION

This chapter describes the calculation for each injury criteria used within Euro NCAP, including the filters that are applied to each channel used in these calculations. The analysis software used by the Euro NCAP labs will follow these calculations in detail.

2.1 Head criteria

2.1.1 Head Resultant Acceleration

The Head Resultant Acceleration is calculated with the following formula:

$$A_R = \sqrt{A_x^2 + A_y^2 + A_z^2}$$

with:

A_x	Filtered Head Acceleration A_x	??HEAD0000??ACXA
A_y	Filtered Head Acceleration A_y	??HEAD0000??ACYA
A_z	Filtered Head Acceleration A_z	??HEAD0000??ACZA

2.1.2 HIC₁₅

The HIC₁₅ value is calculated with the following formula:

$$HIC_{15} = (t_2 - t_1) \left(\frac{1}{(t_2 - t_1)} \int_{t_1}^{t_2} A_R dt \right)^{2.5}$$

with:

A_R	Head Resultant Acceleration
-------	-----------------------------

2.1.3 Head Restraint Contact Time

The Head Restraint Contact Time is calculated with the following formula:

$$T_{HRC} = T_{HRC,end} - T_{HRC,start}$$

with:

$T_{HRC,start}$	Time of first contact of head and HR after T=0	??HERE000000EV00
$T_{HRC,end}$	Time where contact is lost	??HERE000000EV00

Gaps up to 1ms are ignored if proven to be the result of poor electrical contact.

2.1.4 T1 x-acceleration

The T1 x-acceleration value is calculated with the following formula:

$$T1 = \frac{T1_{left} + T1_{right}}{2}$$

with:

T1 _{left}	Filtered left T1 acceleration	??THSP01LEBRACXD
T1 _{right}	Filtered right T1 acceleration	??THSP01RIBRACXD

2.2 **Neck criteria**

2.2.1 Neck extension bending moment

The Neck extension bending moment is calculated with the following formula:

$$M_{OCy} = M_y - F_x \cdot d$$

with:

M _y	Filtered Bending Moment	??NECKUP00??MOYB
F _x	Filtered Shear Force	??NECKUP00??FOXB
d	0.01778m for HIII-50M and HIII-05F	

2.2.2 NIC

The NIC value is calculated with the following formula:

$$NIC = 0.2 \cdot A_{rel} + v_{rel}^2$$

with:

$$A_{rel} = T1 - A_{x,head}$$

$$v_{rel} = A_{rel}$$

T1	Average T1 acceleration	
A _{x,head}	Filtered Head Acceleration A _x	??HEAD0000BRACXD

2.2.3 Nkm

The Nkm value is calculated with the following formula:

$$Nkm(t) = N_{ep}(t) + N_{ea}(t) + N_{fp}(t) + N_{fa}(t)$$

with:

$$N_{ep}(t) = \frac{M_{ye}(t)}{-47.5} + \frac{F_{xp}(t)}{-845}$$

$$N_{ea}(t) = \frac{M_{ye}(t)}{-47.5} + \frac{F_{xa}(t)}{845}$$

$$N_{fp}(t) = \frac{M_{yf}(t)}{88.1} + \frac{F_{xp}(t)}{-845}$$

$$N_{fa}(t) = \frac{M_{yf}(t)}{88.1} + \frac{F_{xa}(t)}{845}$$

$$M_{OCy}(t) = M_y(t) - D \cdot F_x(t)$$

$F_x(t)$	Filtered Upper Neck Shear Force F_x	??NECKUP00BRFOXB
$M_y(t)$	Filtered Upper Neck Moment M_y	??NECKUP00BRMOYB
D	0.01778m	

$F_{xp}(t)$	negative portion of $F_x(t)$
$F_{xa}(t)$	positive portion of $F_x(t)$
$M_{ye}(t)$	negative portion of $M_{OCy}(t)$
$M_{yf}(t)$	positive portion of $M_{OCy}(t)$

2.3 **Shoulder criteria**

2.3.1 Lateral Shoulder Force

The Lateral Shoulder Force is calculated with the following formula:

$$F_{y_{shoulder}} = \max(F_y(t))$$

with:

F_y	Filtered Shoulder Force F_y	??SHLD[LE,RI]00WSFOYB
-------	-------------------------------	-----------------------

2.3.2 Lateral Shoulder Rib Displacement

The Lateral Shoulder Rib Displacement is calculated with the following formula:

$$Dy_{shoulder} = \max(D_y(t) - D_y(0))$$

with:

$$D_y(t) = L(t) \cdot \cos(\alpha(t))$$

L(t)	Filtered Shoulder IR-TRACC length	??SHRI[LE,RI]00WSDS0C
$\alpha(t)$	Filtered Shoulder IR-TRACC rotation	??SHRI[LE,RI]00WSANZC
$D_y(0)$	Lateral Shoulder Rib Displacement @ t=0	

2.4 **Chest criteria**

2.4.1 Chest Deflection

The Chest Deflection value is calculated with the following formula:

$$D_{chest} = \max(D_{chest}(t))$$

with:

$D_{chest}(t)$	Filtered Chest Deflection D_{chest}	??CHST0003??DSXC
----------------	---------------------------------------	------------------

2.4.2 Seatbelt force modifier

The Seatbelt force modifier is calculated with the following formula:

$$MA_{seatbelt} = \max(MA_{seatbelt}(t))$$

with:

$$MA_{seatbelt}(t) = \frac{1}{2n+1} \sum_{j=t-n}^{j=t+n} F_{seatbelt}(j)$$

$F_{seatbelt}$	Filtered Seatbelt Force	??SEBE0003B3FO0D
n	number of samples equivalent to 10ms	

2.4.3 Lateral Thoracic Rib Displacement

The Lateral Thoracic Rib Displacement is calculated with the following formula:

$$Dy_{thorax} = \max(D_y(t) - D_y(0))$$

with:

$$D_y(t) = L(t) \cdot \cos(\alpha(t))$$

L(t)	Filtered Thoracic IR-TRACC length	??TRRI[LE,RI]01WSDS0C
$\alpha(t)$	Filtered Thoracic IR-TRACC rotation	??TRRI[LE,RI]01WSANZC
$D_y(0)$	Lateral Thoracic Rib Displacement @ t=0	

2.4.4 Viscous Criterion

The VC is calculated with the following formula:

$$VC = sf \cdot V(t) \times C(t)$$

With:

sf 1.3 for HIII-50M, 1.3 for HIII-05F and 1.0 for WorldSID

$$V(t) = \frac{8(D_{chest}(t+1) - D_{chest}(t-1)) - (D_{chest}(t+2) - D_{chest}(t-2))}{12\Delta t}$$

$$C(t) = \frac{D_{chest}(t)}{D_{constant}}$$

$D_{chest}(t)$ Filtered Chest Deflection D_{chest} ??CHST0003??DSXC
for WorldSID use calculated Lateral Thoracic Rib Displacement $D_{y_{thorax}}$

Δt Time step

$D_{constant}$ 0.229 for HIII-50M, 0.187 for HIII-05F and 0.170 for WorldSID

2.5 **Abdomen criteria**

2.5.1 T12 Resultant Acceleration

The T12 Resultant Acceleration is calculated with the following formula:

$$A_R = \sqrt{A_x^2 + A_y^2 + A_z^2}$$

with:

A_x Filtered T12 Acceleration A_x ??THSP1200WSACXC

A_y Filtered T12 Acceleration A_y ??THSP1200WSACYC

A_z Filtered T12 Acceleration A_z ??THSP1200WSACZC

2.5.2 Lateral Abdominal Rib Displacement

The Lateral Abdominal Rib Displacement is calculated with the following formula:

$$D_{y_{abdomen}} = \max(D_y(t) - D_y(0))$$

with:

$$D_y(t) = L(t) \cdot \cos(\alpha(t))$$

$L(t)$ Filtered Abdominal IR-TRACC length ??ABRI[LE,RI]01WSDS0C

$\alpha(t)$ Filtered Abdominal IR-TRACC rotation ??ABRI[LE,RI]01WSANZC

$D_y(0)$ Lateral Abdominal Rib Displacement @ t=0

2.6 Lower extremities criteria

2.6.1 Iliac Force Drop

The Iliac Force Drop value is calculated with the following formula:

$$IFD = \max(IFD(t))$$

With:

$$IFD(t) = F_{iliac}(t) - F_{iliac}(t - 0.001)$$

$F_{iliac}(t)$ Filtered Iliac Force F_{iliac} ??ILAC[LE,RI]00??FOXB

2.6.2 Knee Displacement

The Knee Displacement value is calculated with the following formula:

$$D_{knee} = |\min(D_{knee}(t))|$$

With:

$D_{knee}(t)$ Filtered Knee Displacement D_{knee} ??KNSL[LE,RI]00??DSXC

2.6.3 Femur Force

The Femur Force value is calculated with the following formula:

$$F_{femur} = \max(F_{femur}(t))$$

With:

$F_{femur}(t)$ Filtered Femur Force F_{femur} ??FEMR[LE,RI]00HFFOZB

2.6.4 Tibia Index

The Tibia Index is calculated with the following formula:

$$TI(t) = \left(\frac{M_R(t)}{(M_R)_C} \right) + \left(\frac{F_z(t)}{(F_z)_C} \right)$$

with:

$$M_R(t) = \sqrt{M_x(t)^2 + M_y(t)^2}$$

M_x Filtered Bending Moment M_x ??TIBI[LE,RI][UP,LO]??MOXB

F_z Filtered Bending Moment F_z ??TIBI[LE,RI][UP,LO]??FOZB

$(M_R)_C$ 225Nm for HIII-50M and 115Nm for HIII-05F

$(F_z)_C$ 35.9N for HIII-50M and 22.9N for HIII-05F