



GEELY STARRAY EM-i
Standard Safety Equipment

2025



Adult Occupant



90%

Child Occupant



87%

Vulnerable Road Users



86%

Safety Assist



77%

SPECIFICATION

| | |
|-------------------------------|-----------------------------------|
| Tested Model | GEELY STARRAY EM-i 'Comfort', LHD |
| Body Type | - 5 door SUV |
| Year Of Publication | 2025 |
| Kerb Weight | 1750kg |
| VIN From Which Rating Applies | - all STARRAY EM-i |
| Class | Small SUV |

SAFETY EQUIPMENT

| | Driver | Passenger | Rear |
|--------------------------|--------|-----------|------|
| FRONTAL CRASH PROTECTION | | | |
| Frontal airbag | ● | ● | — |
| Belt pretensioner | ● | ● | ● |
| Belt loadlimiter | ● | ● | ● |
| Knee airbag | ✗ | ✗ | — |
| LATERAL CRASH PROTECTION | | | |
| Side head airbag | ● | ● | ● |
| Side chest airbag | ● | ● | ✗ |
| Side pelvis airbag | ● | ● | ✗ |
| Centre Airbag | ● | ✗ | — |

| | Driver | Passenger | Rear |
|--------------------------|--------|-----------|------|
| CHILD PROTECTION | | | |
| Isofix/i-Size | — | ● | ● |
| Integrated CRS | — | ✗ | ✗ |
| Airbag cut-off switch | — | ● | — |
| Child presence detection | — | ✗ | ● |
| SAFETY ASSIST | | | |
| Seat Belt Reminder | ● | ● | ● |

SAFETY EQUIPMENT (NEXT)

| OTHER SYSTEMS | | |
|---------------------------------|--|---|
| Active Bonnet | | ✖ |
| AEB Vulnerable Road Users | | ● |
| AEB Pedestrian - Reverse | | ● |
| Cyclist Dooring Prevention | | ● |
| AEB Motorcyclist | | ● |
| AEB Car-to-Car | | ● |
| Speed Assistance | | ● |
| Lane Assist System | | ● |
| Fatigue / Distraction Detection | | ● |

Note: Other equipment may be available on the vehicle but was not considered in the test year.

- Fitted to the vehicle as standard
- Fitted to the vehicle as part of the safety pack
- Not fitted to the test vehicle but available as option or as part of the safety pack
- ✖ Not available
- Not applicable

 ADULT OCCUPANT

Total 36.2 Pts / 90%

GOOD ADEQUATE MARGINAL WEAK POOR

Frontal Impact

13.3 / 16 Pts



Mobile Progressive Deformable Barrier



Full Width Rigid Barrier

Lateral Impact

15.9 / 16 Pts




Side Mobile Barrier



Side Pole



Far-Side Excursion



Occupant Interaction

Rear Impact

4.0 / 4 Pts



Rear Seat



Front Seat

 ADULT OCCUPANT

Total 36.2 Pts / 90%


GOOD

ADEQUATE

MARGINAL

WEAK

POOR

| | | |
|------------------------|--------------------------|---|
| Rescue and Extrication | | 3.0 / 4 Pts |
| Rescue Sheet | Available, ISO compliant |  |
| Advanced eCall | Available | |
| Multi Collision Brake | Available | |
| Submergence Check | Compliant | |

Comments

The passenger compartment of the GEELY STARRAY EM-i remained stable in the frontal offset test. Dummy readings indicated good protection of the knees and femurs of both the driver and the front seat passenger. GEELY showed that a similar level of protection would be provided to occupants of different sizes and to those sitting in different positions. Analysis of the deceleration of the impact trolley during the test, and analysis of the deformable barrier after the test, revealed that the GEELY STARRAY EM-i would be a moderately benign impact partner in a frontal collision. In the full-width rigid barrier test, protection was good or adequate for all critical body regions of the driver rear seat passenger. In the side barrier test, the GEELY STARRAY EM-i provided good protection to all critical body areas and scored maximum points. In the more severe side pole impact, protection was at least adequate for all critical body areas. Control of excursion (the extent to which a body is thrown to the other side of the vehicle when it is hit from the far side) was found to be adequate. The GEELY STARRAY EM-i has a countermeasure to mitigate against occupant-to-occupant injuries in such impacts. The airbag performed well in Euro NCAP's tests with dummy readings indicating good protection for both the driver and passenger. Tests on the front seats and head restraints demonstrated good protection against whiplash injuries in the event of a rear-end collision. A geometric analysis of the rear seats also indicated good whiplash protection. The car has an advanced eCall system which alerts the emergency services in the event of a crash, and a system to prevent secondary impacts after the car has been in a collision. GEELY demonstrated that the doors and windows would be openable to allow occupants to escape in the event of vehicle submergence.

 CHILD OCCUPANT

Total 42.7 Pts / 87%

GOOD ADEQUATE MARGINAL WEAK POOR

Crash Test Performance based on 6 & 10 year old children 24.0 / 24 Pts

Frontal Impact16 Pts



Lateral Impact8 Pts







Restraint for 6 year old child: *Cybex T Solution i-Fix*
Restraint for 10 year old child: *Osann Booster Basic R129*



Safety Features 7.0 / 13 Pts

| | Front Passenger | 2nd row outboard | 2nd row center |
|--------------------------|-----------------|------------------|----------------|
| Isofix | ● | ● | ✗ |
| i-Size | ● | ● | ✗ |
| Integrated CRS | ✗ | ✗ | ✗ |
| Top tether | ● | ● | ✗ |
| Child Presence Detection | ✗ | ● | ● |

● Fitted to test car as standard ○ Not on test car but available as option ✗ Not available










CRS Installation Check 11.7 / 12 Pts

|  i-Size | Seat Position | | | | |
|--|---|---|---------|--------|-------|
| | Front | | 2nd row | | |
| |  |  | Left | center | Right |
|  | ● | ● | ● | — | ● |



● Easy ● Difficult ● Safety critical ✗ Not allowed
 Airbag ON Rearward facing restraint installation not allowed  Airbag OFF









 CHILD OCCUPANT

Total 42.7 Pts / 87%



|  Isofix | Seat Position | | | | |
|--|---|---|---------|--------|-------|
| | Front | | 2nd row | | |
| |  |  | Left | center | Right |
|  | ● | ● | ● | — | ● |
|  | ✗ | ● | ● | — | ● |
|  | ● | ● | ● | — | ● |
|  | ● | ● | ● | — | ● |
|  | ● | ● | ● | — | ● |
|  | ✗ | ● | ● | — | ● |

● Easy ● Difficult ● Safety critical ✗ Not allowed

 Airbag ON Rearward facing restraint installation not allowed  Airbag OFF

| Seatbelt Attached | Seat Position | | | | |
|---|---|---|---------|--------|-------|
| | Front | | 2nd row | | |
| |  |  | Left | center | Right |
|  | ✗ | ● | ● | ● | ● |
|  | ● | ● | ● | ● | ● |
|  | ● | ● | ● | ● | ● |
|  | ● | ● | ● | ● | ● |
|  | ● | ● | ● | ● | ● |
|  | ✗ | ● | ● | ● | ● |

● Easy ● Difficult ● Safety critical ✗ Not allowed

 Airbag ON Rearward facing restraint installation not allowed  Airbag OFF

 CHILD OCCUPANT

Total 42.7 Pts / 87%

Comments

In both the frontal offset and the side barrier tests, protection was good for all critical body areas for the 6 and 10 year dummies, and the GEELY STARRAY EM-i scored maximum points in this part of the assessment. The front passenger airbag can be disabled to allow a rearward-facing child restraint to be used in that seating position. Clear information is provided to the driver regarding the status of the airbag and the system was rewarded. The GEELY STARRAY EM-i is equipped with a direct 'child presence detection' system, which issues a warning when it detects that a child or infant has been left in the car. The largest i-Size restraint, for children from 100 to 135cm, could not be properly installed in the front passenger seat owing to interference with the seat foam. Otherwise, all child restraint types for which the STARRAY EM-i is designed could be installed and accommodated.



VULNERABLE ROAD USERS

Total 54.4 Pts / 86%

GOOD

ADEQUATE

MARGINAL

WEAK

POOR

VRU Impact Protection

30.9 / 36 Pts



| | |
|---------------------------|----------|
| Pedestrian & Cyclist Head | 13.2 Pts |
| Pelvis | 4.2 Pts |
| Femur | 4.5 Pts |
| Knee & Tibia | 9.0 Pts |

VRU Impact Mitigation

23.7 / 27 Pts

| | |
|------------------|---|
| System Name | Collision Mitigation Support Front |
| Type | Auto-Brake with Forward Collision Warning |
| Operational From | 10 km/h |
| PERFORMANCE | |

AEB Pedestrian

7.5 / 9 Pts

| Scenario | Day time | Night time |
|---|----------|------------|
| Car reversing into adult or child | | — |
| Adult crossing a road into which a car is turning | | — |
| Adult crossing the road | | |
| Child running from behind parked vehicles | | |
| Adult along the roadside | | |

— Currently not tested

AEB Cyclist

7.4 / 8 Pts

| Scenario | Day time |
|--|----------|
| Approaching cyclist crossing from behind parked vehicles | |
| Turning across path of an oncoming cyclist | |
| Approaching a crossing cyclist | |
| Approaching a cyclist along the roadside | |



VULNERABLE ROAD USERS

Total 54.4 Pts / 86%

GOOD

ADEQUATE

MARGINAL

WEAK

POOR

Cyclist Dooring Prevention

0.3 / 1 Pts

| Scenario | |
|---------------------------|--------------------------------|
| Dooring a passing cyclist | information, driver door only" |

AEB Motorcyclist

6.0 / 6 Pts

| Scenario | Autobrake function only | Driver reacts to warning |
|--|-------------------------|--------------------------|
| Approaching a stationary motorcyclist | | |
| Approaching a braking motorcyclist | | |
| Turn across the path of an oncoming motorcyclist | | — |

— Currently not tested

Lane Support Motorcyclist

2.5 / 3 Pts

| Scenario | Day time |
|---|----------|
| Changing lane across the path of an oncoming motorcyclist | |
| Changing lane across the path of an overtaking motorcyclist | |

Comments

Protection of the head of a struck pedestrian or cyclist was largely good or adequate, with poor results recorded on the stiff windscreen pillars and at the base and top of the screen. Protection of the pelvis was good or adequate at all test locations. Protection of the femur and that of the knee and tibia was good at all test locations. The autonomous emergency braking system of the GEELY STARRAY EM-i responds to vulnerable road users such as pedestrians and cyclists, as well as to other vehicles. In tests of its response to pedestrians, the system performed well overall, with adequate protection for those to the rear of the car. The system performed well in tests of its reaction to cyclists, including some protection against 'dooring', where a door is opened into the path of a cyclist approaching from behind. The system's response to motorcyclists was good.

 SAFETY ASSIST

Total 14.0 Pts / 77%

GOOD

ADEQUATE

MARGINAL

WEAK

POOR

Speed Assistance 1.5 / 3 Pts

| | |
|----------------------------------|-------------------------------------|
| System Name | Speed Assistance System |
| Speed Limit Information Function | Camera & Map, subsigns supported |
| Speed Limitation Function | Intelligent ACC (accurate to 5km/h) |

Occupant Status Monitoring 2.3 / 3 Pts

> Seatbelt Reminder

 1.0 / 1 Pts

| Applies To | Front and rear seats | | |
|--------------------|----------------------|--------------------|-------------------|
| Warning | Driver Seat | Front Passenger(s) | Rear Passenger(s) |
| Visual | <div></div> | <div></div> | <div></div> |
| Audible | <div></div> | <div></div> | <div></div> |
| Occupant Detection | <div></div> | <div></div> | <div></div> |

Pass Fail Not available

> Driver Monitoring

 1.3 / 2 Pts

| | |
|------------------|--|
| System Name | Driver Performance Support |
| Type | Direct eye monitoring |
| Operational From | 10 km/h |
| Fatigue | Drowsiness, Microsleep and Sleep |
| Distraction | Long & Short Distraction and Phone Use |

 SAFETY ASSIST

Total 14.0 Pts / 77%

Lane Support 3.0 / 3 Pts

| | |
|-------------------------|---------------------------|
| System Name | Lane Keeping Assist (LKA) |
| Type | LKA and ELK |
| Operational From | 65 km/h |
| PERFORMANCE | |
| Emergency Lane Keeping | GOOD |
| Lane Keep Assist | GOOD |
| Human Machine Interface | GOOD |

AEB Car-to-Car 7.3 / 9 Pts

| | |
|------------------|--|
| System Name | Autonomous Emergency Brake |
| Type | Autonomous emergency braking and forward collision warning |
| Operational From | 4 km/h |
| Sensor Used | camera |

| Scenario | Autobrake function only | Driver reacts to warning |
|--|-------------------------|--------------------------|
| Approaching a car crossing a junction | | |
| Approaching a car head-on | | |
| Turning across the path of an oncoming car | | |
| Approaching a stationary car | | |
| Approaching a slower moving car | | |
| Approaching a braking car | | |

Currently not tested



SAFETY ASSIST

Total 14.0 Pts / 77%

Comments

Overall, the performance of the autonomous emergency braking (AEB) system was good in tests of its reaction to other vehicles. A seatbelt reminder system is fitted as standard to the front and rear seats. The car has a direct driver status monitoring system as standard, detecting driver fatigue and some types of distraction. The lane support system gently corrects the vehicle's path if it is drifting out of lane and also intervenes in some more critical situations. The speed assistance system identifies the local speed limit. The driver can choose to allow the limiter to be set automatically by the system.

RATING VALIDITY



Variants of Model Range

| Body Type | Engine | Model Name | Drivetrain | Rating Applies | |
|------------|-------------|---------------------|------------|----------------|-----|
| | | | | LHD | RHD |
| 5 door SUV | Petrol PHEV | Comfort * Techno | 4 x 2 | | |

* Tested variant

Annual Reviews and Facelifts

| Date | Event | Outcome | |
|---------------|------------------|---------|--|
| December 2025 | Rating Published | 2025 | |